



FAG BEARING LIMITED



40 mm x 90 mm x 33 mm KOYO NU2308R cylindrical roller bearings

Bearing No. NU2308R

| | |
|-------------------------------|-------------|
| Size | 40x90x33 mm |
| Bore Diameter | 40 mm |
| Outer Diameter | 90 mm |
| Width | 33 mm |
| d | 40 mm |
| Fw | 52 mm |
| D | 90 mm |
| B | 33 mm |
| C | 33 mm |
| r min. | 1.5 mm |
| r1 min. | 1.5 mm |
| Weight | 0.962 Kg |
| Basic dynamic load rating (C) | 114 kN |
| Basic static load rating (C0) | 122 kN |
| (Grease) Lubrication Speed | 6100 r/min |
| Bearing No. | NU2308R |
| r(min) | 1.5 |
| r1(min) | 1.5 |
| Cr | 143 |
| C0r | 122 |
| Cu | 18.4 |
| Grease lub. | 6100 |
| Oil lub. | 9100 |
| Ew | - |
| d1 | - |

NU2308R Bearing 2D drawings and 3D CAD models



FAG BEARING LIMITED

| | |
|------------------|-------|
| B1 | - |
| B2 | - |
| da(min) | - |
| db(min) | 48 |
| db(max) | 51 |
| dc(min) | - |
| dd(min) | - |
| Da(max) | 82 |
| Db(max) | - |
| Db(min) | - |
| ra(max) | 1.5 |
| rb(max) | 1.5 |
| (Refer.)Mass(kg) | 0.962 |